



SYMBOL LS3408-ER

EXTENDED RANGE RUGGED SCANNER

REDEFINING PERFORMANCE FOR MAXIMUM INDUSTRIAL MOBILITY

The rugged LS3408-ER handheld scanner delivers superior performance and versatility for your scan-intensive industrial applications. In the yard, warehouse, distribution center, manufacturing plant or retail store, the LS3408-ER handheld scanner offers best-in-class performance, excellent reliability and user-friendly ergonomics to create a more productive mobile environment. Multiple on-board interfaces ensure flexible plug and play host connectivity.

ADVANCED DATA CAPTURE FEATURES FOR INDUSTRIAL-GRADE APPLICATIONS

The LS3408-ER offers an outstanding reading range, providing the flexibility to enable a wide range of industrial applications. Industry leading impact tests ensure reliable performance in spite of the inevitable accidental drops. The device is impervious to dust and water, and its exit window is scratch-resistant and recessed for the highest level of durability. As a result, you avoid unnecessary equipment downtime or expensive equipment replacement costs. For applications requiring quick access and convenient storage, the LS3408-ER features a built-in metal hook for attachment to a pulley. Two large LED-enhancing windows and an extra loud 80 decibel (db) beeper are strategically placed on the scanner for clear and audible feedback to users.

THE SMARTEST WAY TO CAPTURE MISSION CRITICAL INFORMATION

The extended range LS3408-ER is designed specifically for industrial applications. When you choose the LS3408-ER, you receive the added assurance of purchasing from Zebra a company with proven advanced data capture capabilities and millions of scanner installations worldwide.

FEATURES

Wide working range:
.25/.64 cm to 45 ft./
13.7 m

Improves user productivity

Ergonomic, rugged industrial design withstands up to 50 drops to concrete from 6.5 ft. (2m) and 2,500 3 ft. (1m) tumbles (5,000 hits)

Ensures maximum reliability with less down time due to accidental drops

IP65 sealing rating (electronic enclosure)

Protects against water and dust to ensure reliable performance in rough conditions

Bright 650nm laser aiming dot

Delivers clearly visible line for more accurate scanning

Dual-scan angle switches from

For more information on how the LS3408-ER can benefit your business, please visit us on the web at www.zebra.com/ls3408er or access our global contact directory at www.zebra.com/contact.

**standard to wide
under software
control**

Offers fast, accurate bar code reading on menus and pick lists

**Multiple on-board
interfaces**

Ensures flexible connectivity, allowing for host future proofing

**Advanced data
formatting (ADF)**

Eliminates costly modifications to the host software

Flash memory

Facilitates updates and customization of product in the field

Universal cable set

Allows for easy replacement and/or upgrades

**Supports GS1DataBar
Symbolologies (
formerly RSS)**

Compatible with emerging symbology to leverage your hardware investment

SPECIFICATIONS CHART

PHYSICAL CHARACTERISTICS		USER ENVIRONMENT	
Dimensions	7.34 in. H x 4.82 in. W x 2.93 in. D 18.65 cm H x 12.25 cm W x 7.43 cm D	Operating Temp.	-22° to 122° F/-30° to 50° C
Weight (w/o cable)	Weight (w/o cable) 12.56 oz./356 g	Storage temperature	-40 to 158F (-40 to 70C)
Power Requirements	4.5 - 14 VDC	Humidity	5% to 95% relative humidity, noncondensing
Stand-by Current	50 mA	Sealing	Sealed to IP65 specifications
Power Sources	Depending on host: Host power External power supply	Drop specifications	Unit functions normally after 50 drops to concrete from 6.5 ft. (2m)
Color	Twilight Black/Yellow	Ambient lighting tolerance	Tolerant to typical artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED4: 450 Ft Candles (4,844 Lux) Sunlight: 8000 Ft Candles (43,040 Lux)
PERFORMANCE CHARACTERISTICS		Electrostatic discharge	Conforms to 20 kV air discharge and 8 kV of contact discharge
Scanner type	Retrocollective	REGULATORY	
Light source	650 nm visible laser diode	Input transient protection	IEC 1000-4-(2,3,4,5,6,11)
Scan repetition	36 scans per second typical	EMI/RFI	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Japan VCCI/MITI/Dentori
Minimum element width	7.5 mil (0.191 mm)	Laser safety	IEC825-1 Class 2
Nominal working distance	See decode zone	WARRANTY	
Print contrast	25% minimum reflective difference	The LS3408-ER is warranted against defects in workmanship and materials for a period of 3 years (36 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty for details.	
Roll (Tilt) ¹	+/- 10 degrees from normal	RECOMMENDED SERVICES	
Pitch ²	+/- 65 degrees from normal	Support Services	Service from the Start - Bronze
Skew (Yaw) ³	+/- 60 degrees from normal		
Decode capability	UPC/EAN, UPC/EAN with Supplementals, GS1-128 (formerly UCC/EAN 128), JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, GS1DataBar (formerly RSS)		
Interfaces supported	RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation,		
		1- Roll (Tilt): Controlled by rotating the wrist clockwise or counterclockwise	

IBM 468X/469X, USB and
Synapse

- 2- Pitch: Controlled by dropping or raising the wrist
- 3- Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa
- 4- LED lighting with high AC ripple content can impact scanning performance

DEPTH OF FIELD		
LABEL DENSITY	LS3408-ER	
Paper Label	English	Metric
Code 39 7.5 mil	0.25 20.00	0.64 50.80 cm
Code 39 10 mil	2.00 32.00	5.08 81.28 cm
Code 39 15 mil	3.00 69.00	7.62 175.26 cm
Code 39 20 mil	3.00 94.00	7.62 238.76 cm
Code 39 55 mil	15.00 180.00	38.10 457.20 cm
REFLECTIVE LABEL		
Code 39 70 mil	Up to 30 ft.	Up to 9.27 m
Code 39 100 mil	Up to 45 ft.	Up to 13.72 m

For more detailed information, please see the Product Reference Guide in the Resource tab at www.zebra.com/ls3408er

CN410 CE



ZEBRA

Part number: SS-LS3408. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. SYMBOL is a trademark owned by Symbol Technologies, Inc., which is an indirect wholly owned subsidiary of Zebra Technologies Corporation. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES